

DUPLEX BOARD GREY BACK (GD2)



Alimentació



Gràfica



Higiene



Neteja



Packaging
genèric



Productes
electrònics



Sector Industrial

ESPECIFICACIONS TÈCNIQUES

GRAMATGE (g/m ²) (ISO 536)	GRUIX (mm) (ISO 534)	RIGIDESA TABER 15° (mNm) (ISO 2493)	RIGIDESA TABER 15° (mNm)
		DT	DM
200	240±20	2.2	4.2
220	265±20	2.7	5.4
230	275±20	2.9	5.9
240	285±20	3.2	6.4
250	305±20	3.4	6.9
260	315±20	3.7	7.4
270	340±20	4.4	8.8
280	355±20	5.4	10.8
300	385±25	5.9	11.8
320	410±25	6.4	13.7
330	425±25	6.9	15.2
350	455±25	8.8	17.7
400	520±25	12.3	24.5
450	GRUIX (mm)(ISO 534)	17.2	34.3
480		22.1	44.1
	590±25		
	630±30		

PROPIEDADES

BLANCURA (ISO 7026) (%)

des-23

El fabricant del material es reserva el dret a fer modificacions sense previ avís.
Certificat de Cadena de Custòdia CU-COC-821792 per poder servir aquest material certificat FSC