# METSÄBOARD PRIME WKL (KRAFLINER COATED 1 SIDE)

Kraftliner with a double coating on the top side. It is specially developed for printing halftone and color images with brilliance and color density. Its smooth surface allows for more detailed and uniform printed images. Printing methods: Sheet-fed offset printing, Flexographic prepress.

### Printing methods

Offset
Inkjet Digital Printing
Flexographic Pre-Post Printing


Electronic Products


Food


Generic Packaging

## TECHNICAL SPECIFICATIONS

| | WEIGHT (g/m²) (ISO 536) | THICKNESS (mm) (ISO 534) | TABER RIGIDITY 15° (mNm) (ISO 2493) | TABER RIGIDITY 15° (mNm) |
|---|---|---|---|---|
| | | | DT | DM |
| | 125 | 120 | 2.8 | 1.4 |
| | 135 | 135 | 3.0 | 1.5 |
| | 145 | 145 | 3.1 | 1.6 |
| | 160 | 165 | 3.3 | 1.6 |
| | 170 | 175 | 3.4 | 1.7 |
| | 185 | 190 | 3.6 | 1.8 |
| | 250 | 250 | 4.5 | 2.6 |

## PROPIEDADES

| | |
|---|---|
| | PLAY BOND (J/m2) (TAPPI T 569) |
| | COBB 1 min (g/m2) (ISO535) |
| | BRIGHTNESS (%) (ISO8254-1) |

Aug - 23

The manufacturer of the material reserves the right to make changes without prior notice
PEFC Chain of Custody Certificate No. CU-PEFC-COC-821792 to be able to serve this PEFC Certified material.