

# METSÄBOARD PRIME WKL (KRAFLINER COATED 1 SIDE)



Kraftliner with a double coating on the top side. It is specially developed for printing halftone and color images with brilliance and color density. Its smooth surface allows for more detailed and uniform printed images. Printing methods: Sheet-fed offset printing, Flexographic prepress.

## Printing methods

Offset  
Inkjet Digital Printing  
Flexographic Pre-Post  
Printing



Electronic Products



Food



Generic Packaging

## TECHNICAL SPECIFICATIONS

WEIGHT (g/m <sup>2</sup> ) (ISO 536)	THICKNESS (mm) (ISO 534)	TABER RIGIDITY 15° (mNm) (ISO 2493)	
		DT	DM
125	120	2.8	1.4
135	135	3.0	1.5
145	145	3.1	1.6
160	165	3.3	1.6
170	175	3.4	1.7
185	190	3.6	1.8
250	250	4.5	2.6

## PROPIEDADES

PLAY BOND (J/m<sup>2</sup>) (TAPPI T 569)

COBB 1 min (g/m<sup>2</sup>) (ISO535)

BRIGHTNESS (%) (ISO8254-1)

Aug - 23

The manufacturer of the material reserves the right to make changes without prior notice  
PEFC Chain of Custody Certificate No. CU-PEFC-COC-821792 to be able to serve this PEFC Certified material.