

WOOD BACK CARDBOARD (GT2)

Triple-layer recycled cardboard (GT2) with double coating on the front and color coating on the back. Used for the manufacture of food, pharmaceutical, and other packaging.



Cleaning



Food



Generic
Packaging



Graphics



Hygiene



Parapharmacy



Pharmacy

TECHNICAL SPECIFICATIONS

| WEIGHT (g/m ²) (ISO 536) | THICKNESS (mm) (ISO 534) | TABER RIGIDITY 15° (mNm) (ISO 2493) | TABER RIGIDITY 15° (mNm) |
|---|-----------------------------|---|-----------------------------|
| | | DT | DM |
| 250 | 338 | 4.2 | 9.1 |
| 275 | 375 | 5.2 | 11.6 |
| 300 | 407 | 6.4 | 14.3 |
| 325 | 445 | 8.1 | 18.1 |
| 350 | 485 | 9.9 | 22.1 |
| 375 | 530 | 11.9 | 26.6 |
| 400 | 555 | 14.3 | 32.0 |
| 425 | 585 | 16.8 | 38.0 |
| 450 | 620 | 19.0 | 43.4 |

PROPIEDADES

WHITENESS (ISO2470) (%)

feb-23

The manufacturer of the material reserves the right to make changes without prior notice.
POSSIBILITY: Chain of Custody Certificate CU-COC-821792 to be able to serve this FSC certified material.