# WHITE BACK CARDBOARD (GT1)

Triple-layer recycled cardboard (GT1) with double coating on the face and white coating on the back. Used for the factory


Cleaning


Cosmetics


Food


Graphics


Hygiene


Parapharmacy


Pharmacy

## TECHNICAL SPECIFICATIONS

| | WEIGHT (g/m²) (ISO 536) | THICKNESS (mm) (ISO 534) | TABER RIGIDITY 15° (mNm) (ISO 2493) | TABER RIGIDITY 15° (mNm) |
|---|---|---|---|---|
| | | | DT | DM |
| | 250 | 338 | 4.2 | 9.1 |
| | 275 | 375 | 5.2 | 11.6 |
| | 300 | 407 | 6.4 | 14.3 |
| | 325 | 445 | 8.1 | 18.1 |
| | 350 | 485 | 9.9 | 22.1 |
| | 375 | 530 | 11.9 | 26.6 |
| | 400 | 555 | 14.3 | 32.0 |
| | 425 | 585 | 16.8 | 38.0 |
| | 450 | 620 | 19.0 | 43.4 |

## PROPIEDADES

| | |
|---|---|
| | WHITENESS (ISO2470) (%) |
| | WHITENESS ON BACK (ISO2470) (%) |

feb-23

The manufacturer of the material reserves the right to make changes without prior notice.
POSSIBILITY: Chain of Custody Certificate CU-COC-821792 to be able to serve this FSC certified material.