

TRB VINCIWHITE (GT1)

Cartón estucado fabricado con fibras recicladas y el reverso blanco.



Printing methods

Offset
Flexografía
Huecograbado



Graphics



Hygiene



Cleaning



Generic Packaging



POS Advertising



Industrial Sector

TECHNICAL SPECIFICATIONS

GRAMAJE (g/m2) (ISO 536)	ESPESOR (µm) (ISO 534)	RIGIDEZ TABER 15° (mNm) (ISO 2493)	RIGIDEZ TABER 15° (mNm) (ISO 2493)
-	-	DM	DT
(260)	345	8.4	3.6
290	378	10.7	4.6
320	415	14.8	6.5
350	448	19.0	8.7
(385)	488	23.7	11.1
400	508	26.8	12.6
450	573	35.2	16.5
TOLERANCIA +/- 2 %	+/- 5 %	-15%	

PROPIEDADES

BLANCURA SUPERFICIE (ISO 2470-2) (%)	82 +/- 2%
BLANCURA REVERSO (ISO 2470-2) (%)	77 +/- 2%

0305018

Junio 2025

El Fabricante del material se reserva el derecho a modificaciones sin previo aviso.

(XXX) Gramaje no estándar.
Certificado de Cadena de Custodia CU-COC-821792 para poder servir este material certificado FSC.