

DUPLEX BOARD GREY BACK (GD2)



Alimentar



Embalagens genéricas



Gráfica



Higiene



Limpeza



Produtos eletrônicos



Setor Industrial

ESPECIFICAÇÕES TÉCNICAS

GRAMAGEM (g/m ²) (ISO 536)	ESPESSURA (mm) (ISO 534)	RIGIDEZ TABER 15° (mNm) (ISO 2493)	RESISTÊNCIA À FLEXÃO 15° (mNm)
		DT	DM
200	240±20	2.2	4.2
220	265±20	2.7	5.4
230	275±20	2.9	5.9
240	285±20	3.2	6.4
250	305±20	3.4	6.9
260	315±20	3.7	7.4
270	340±20	4.4	8.8
280	355±20	5.4	10.8
300	385±25	5.9	11.8
320	410±25	6.4	13.7
330	425±25	6.9	15.2
350	455±25	8.8	17.7
400	520±25	12.3	24.5
450	ESPESSURA (µm) (ISO 534)	17.2	34.3
480		22.1	44.1
	590±25		
	630±30		

PROPIEDADES

BRANQUEAMENTO (ISO 7026) (%)

dez-23

O fabricante do material reserva-se o direito de realizar alterações sem aviso prévio.
Certificado de Cadena de Custodia CU-COC-821792 para poder servir este material certificado FSC